



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com

2013

W. F. WELLS MODEL B-25-2

Specifications

Capacity.....	Rectangular at 90° 25" High x 40" Wide, Round 25.5"	
	Rectangular at 45° 25" High X 24" Wide	
Weight Capacity.....	15,000 lbs	
Blade Speed	60-500 SFPM	
Blade Size	1½" X .050" X 26'-6"	
Blade Guide.....	Spring Tensioned Carbide Blocks with Idle Roller Backup	
Blade Tension.....	Hydraulic	
Bandwheel Size	26"	<u>Voltage</u>
Vise	Hydraulic	208-60-3
Blade Drive	10 HP, AC Vector Drive	230-60-3
Sawing Force.....	0-1,000 lbs	460-60-3
Coolant Capacity	15 Gallons	575-60-3
Hydraulic Capacity	20 Gallons	
Hydraulic Drive	5 HP Motor	
Work Height.....	28"	
Outfeed Table.....	24" X 40"	
Vise Jaw Height.....	17"	
Blade Break/Stall Switch		
Hydraulic Positioned Guide Arm		
Hydraulic Powered Blade Brush		
Electronic Door Interlocks		
Blade Tension Indicator		
Shipping Weight.....	6,600 lbs	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	170" Length x 55" Width x 100" Height	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Discharge Worktable 40" Wide X 56" Long
- Hydraulic Chip Conveyor
- Hydraulic Holddown, Saw Vise
- Outboard Vise with Hydraulic Holddown
- Outboard Vise
- Hydraulic Powered Conveyor 40" X 10'
- High Speed Drive & Guides (1¼" Blade) 500-3000 SFPM
- Non-Powered Conveyor 40" X 5'
- Non-Powered Conveyor 40" X 10'

B-25-2 with Automatic Barfeed see B-25-2A3 CNC

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

Distributed By:

Tool Technology
Distributors, Inc.

P: 510-656-8220
 P: 800-335-8437
 F: 510-656-2458
 E: info@tooltechnology.com
 W: www.tooltechnology.com

MADE IN USA