



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com

2013



W. F. WELLS MODEL B-25-2CA3 CNC (6° CANT)

Specifications

Capacity..... 22" High x 40" Wide (25" Round, 24" Square)
 Weight Capacity..... 14,000 lbs
 Blade Speed 60-500 SFPM
 Blade Size 1½" X .050" X 26' 6"
 Blade Guide Spring Tensioned Carbide Blocks with Idle Roller Backup
 Blade Tension..... Hydraulic
 Bandwheel Size 26"
 Vise Hydraulic
 Blade Drive 10 HP, AC Vector Drive
 Sawing Force..... 0-1,000 lbs
 Coolant Capacity 15 Gallons
 Hydraulic Capacity 20 Gallons
 Hydraulic Drive 5 HP Motor
 Work Height..... 34"
 Outfeed Table 12" X 41"
 Vise Jaw Height 17"
 Barfeed Projection 0-36" CNC Controlled
 Projection Accuracy +/- .002"
 Shuttle Indexes Unlimited
 Remnant End..... 14"
 Electrics Wired to NFPA 79 Machine Tool Standards
 Hydraulic Positioned Guide Arm, Powered Blade Brush, Blade Break/Stall Switch
 CNC Programmable Controlled with Color Touch Screen
 500+ Job Selection
 Automatic Kerf Compensation
 Shipping Weight.....11,000 Shipping Dimensions.....170"L x 102"W x 105"H

Voltage

208-60-3
 230-60-3
 460-60-3
 575-60-3

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Discharge Worktable 40" Wide X 56" Long
 Hydraulic Chip Conveyor
 Hydraulic Holddown, Saw Vise
 Hydraulic Holddown, Barfeed Vise
 Outboard Vise with Hydraulic Holddown
 Outboard Vise
 Non-Powered Conveyor 40" X 5'
 Non-Powered Conveyor 40" X 10'
 High Speed Drive & Guides (1¼" Blade) 500-3000 SFPM

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

