



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013

**W. F. WELLS MODEL B-25-2C (6° Cant)**

**Specifications**

Capacity.....	Rectangular at 90° 22" High X 40" Wide (25" Round, 24" Square)	
	Rectangular at 45° 22" High X 24" Wide	
Weight Capacity.....	15,000 lbs	
Blade Speed .....	60-500 SFPM	
Blade Size .....	1½" X .050" X 26' 6"	
Blade Guide .....	Spring Tensioned Carbide Blocks with Idle Roller Backup	
Blade Tension.....	Hydraulic	
Bandwheel Size .....	26"	<b><u>Voltage</u></b>
Vise .....	Hydraulic	208-60-3
Blade Drive .....	10 HP, AC Vector Drive	230-60-3
Sawing Force.....	0-1,000 lbs	460-60-3
Coolant Capacity .....	15 Gallons	575-60-3
Hydraulic Capacity .....	20 Gallons	
Hydraulic Drive .....	5 HP Motor	
Work Height.....	34"	
Outfeed Table .....	24" X 40"	
Vise Jaw Height .....	17"	
Hydraulic Positioned Guide Arm		
Hydraulic Powered Blade Brush		
Blade Tension Indicator		
Blade Break/Stall Switch		
Electronic Door Interlocks		
Shipping Weight.....	6,800 lbs	
Shipping Dimensions.....	170" L x 55" W x 105" H	
Electrics .....	Wired to NFPA 79 Machine Tool Standards	

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

- Discharge Worktable 40" Wide X 56" Long
- Hydraulic Chip Conveyor, Auger Style
- Hydraulic Holddown, Saw Vise
- Outboard Vise with Hydraulic Holddown
- Outboard Vise
- Hydraulic Powered Conveyor 40" X 10'
- Non-Powered Conveyor 40" X 5'
- Non-Powered Conveyor 40" X 10'
- High Speed Drive & Guides (1¼" Blade) 500-3000 SFPM

B-25-2C with Automatic Barfeed see B-25-2CA3 CNC

**Consult Factory For Additional Accessories**

\*Prices and specifications subject to change without notice

