



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com

2013

W. F. WELLS MODEL B-25-3

Specifications

Capacity.....	Rectangular at 90° 25" High X 40" Wide , Round 25.5"	
	Rectangular at 45° 25" High X 24" Wide	
Weight Capacity.....	15,000 lbs	
Blade Speed.....	60-500 SFPM	
Blade Size.....	2" X .063" X 26'-6"	
Blade Guide.....	Spring Tensioned Carbide Blocks with Idle Roller Backup	
Blade Tension.....	Hydraulic	
Bandwheel Size.....	26"	<u>Voltage</u>
Vise.....	Hydraulic	208-60-3
Blade Drive.....	15 HP, AC Vector Drive	230-60-3
Sawing Force.....	0-1,000 lbs	460-60-3
Coolant Capacity.....	15 Gallons	575-60-3
Hydraulic Capacity.....	20 Gallons	
Hydraulic Drive.....	5 HP Motor	
Work Height.....	28"	
Outfeed Table.....	24" X 40"	
Vise Jaw Height.....	17"	
Blade Tension Indicator		
Blade Break/Stall Switch		
Hydraulic Powered Blade Brush		
Hydraulic Positioned Guide Arm		
Electronic Door Interlocks		
Shipping Weight.....	7,000 lbs	
Electrics.....	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	170" Length x 55" Width x 100" Height	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Discharge Worktable, 40" Wide X 56" Long
 Hydraulic Chip Conveyor, Auger Style
 Hydraulic Holddown, Saw Vise
 Outboard Vise with Hydraulic Holddown
 Outboard Vise
 Free Standing Control Console
 High Speed Drive & Guides (1½" Blade) 500-3000 SFPM
 Hydraulic Powered Conveyor 40" X 10'
 Non-Powered Conveyor 40" X 5'
 Non-Powered Conveyor 40" X 10'

B-25-3 with Automatic Barfeed see B-25-3A3 CNC

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

MADE IN USA