



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013



**W.F. WELLS MODEL H-2024HA-CNC**

**Specifications**

Capacity.....Rectangular at 90° 20" High x 24" Wide, Round 20" Diameter  
 Weight Capacity.....6,500 lbs  
 Blade Speed.....60-500 SFPM  
 Blade Size.....1½" X .050" X 20'-0"  
 Blade Guide.....Roller Guides with Carbide Inserts  
 Vise.....Hydraulic, Full Stroke, 15" High  
 Bandwheel Size.....22"  
 Blade Tension.....Hydraulic  
 Blade Drive.....10 HP, AC Vector Drive  
 Sawing Force.....0-750 lbs  
 Coolant Capacity.....15 Gallons  
 Hydraulic Capacity.....20 Gallons  
 Hydraulic Drive.....2 HP Motor  
 Work Height.....35"  
 Barfeed Projection.....0-25" CNC Controlled  
 Shuttle Indexes.....Unlimited  
 Projection Accuracy.....+/- .002"  
 Remnant End.....4"  
 Linear Rail Travers Head  
 CNC Programmable Controller with Color Touch Screen  
 500+ Job Selection  
 Automatic Kerf Compensation  
 Blade Break/Stall Switch  
 Bed and Vise Wear Strips  
 Shipping Weight.....5,500 lbs  
 Electrics.....Wired to NFPA 79 Machine Tool Standards  
 Machine Dimensions.....122" Length x 101" Width x 93" Height

**Voltage**

208-60-3  
 230-60-3  
 460-60-3  
 575-60-3

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

Hydraulic Holddown, Saw & Barfeed Vise  
 Hydraulic Auger Style Chip Conveyor  
 Discharge Worktable (24" Wide x 48" Long)  
 Work Light, Wired In  
 Extra Coolant Nozzle with Magnetic Base  
 High Speed Drive & Guides (1¼" Blade) 400-3000 SFPM  
 Free Standing Roller Stock Conveyors, 6" Centers:  
 24" X 5' X 5,000 lbs Cap. Distributed Weight  
 24" X 10' X 10,000 lbs Cap. Distributed Weight  
 24" Powered Conveyors

**Consult Factory For Additional Accessories**

\*Prices and specifications subject to change without notice

