



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone: 269-279-5123  
 Fax: 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013



**W. F. WELLS MODEL M-36SV-3 Split Vise Miter Saw**

**Specifications**

Capacity .....22" H X 60" W @ 90°, 22" H X 36" W @ - 45°  
 ..... 22" H X 36" W @ + 45°  
 ..... 22" H X 20" W @ + 60°  
 Frame Cant .....6°  
 Weight Capacity ..... 15,000 lb  
 Blade Speed .....60-500 SFPM  
 Blade Size .....2" X .063" X 30' -0"  
 Blade Guide .....Spring Tensioned Carbide Blocks with Idle Roller Backup  
 Blade Tension .....Hydraulic  
 Bandwheel Size .....26" **Voltage**  
 Vise .....Hydraulic 208-60-3  
 Blade Drive .....15 HP, AC Vector Drive 230-60-3  
 Sawing Force .....0-1,000 lb 460-60-3  
 Coolant Capacity .....15 Gallons 575-60-3  
 Hydraulic Capacity .....20 Gallons  
 Hydraulic Drive .....5 HP Motor  
 Work Height .....40" (Low Option Available)  
 Mist Coolant  
 Hydraulic Positioned Guide Arm  
 Hydraulic Powered Blade Brush  
 Hydraulic Swivel Base with Miter Vise  
 Digital Angle Display  
 In Feed/ Out Feed Roller  
 Free Standing Control Console  
 Blade Break/Stall Switch  
 Electronic Door Interlocks  
 Shipping Weight .....13,500 lb  
 Shipping Dimensions .....200"L x 102"W x 113"H  
 Electrics .....Wired to NFPA 79 Machine Tool Standards

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

Hydraulic Chip Conveyor, Auger Style  
 Laser Shadow Line  
 Hydraulic Holddown, Saw Vise  
 Flood Coolant

**Conveyor Options Available Upon Request**

**Please Contact  
 Factory**

**Consult Factory for Additional Accessories**

\*Prices and specifications subject to change without notice

