



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone: 269-279-5123
 Fax: 269-279-6337
www.wfwells.com

2013



W.F. WELLS MODEL P-50-3

Specifications

Capacity	Rectangular at 90°	50" High x 50" Wide	
Weight Capacity	15,000 lbs		
Blade Speed	60-500 SFPM		
Blade Size	2" X .063" X 37'-8"		
Blade Guide	Carbide Blocks, Spring Tensioned		
Blade Tension	Hydraulic, Console Controlled		<u>Voltage</u>
Blade Sawing Force	Variable 0-1000 lbs		208-60-3
Saw Vise	Hydraulic Full Stroke		230-60-3
Blade Drive	20 HP, 3ph AC Vector		460-60-3
Hydraulic System	20 Gal. Capacity, 5 HP Motor		575-60-3
Coolant System.....	60 Gal. Capacity, 10 GPM Pump		
Work Height	26"		
Shipping Weight.....	21,500 lbs		
Electrics	Wired to NFPA 79 Machine Tool Standards		
LED Blade Speed Indicator			
Hydraulic Guide Arm Positioning			
Blade Break/Stall Switch			
Hydraulic Powered Blade Brush			
Machine Dimensions.....	24' Length x 60" Width x 13'6" Height		

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Discharge Worktable, 50" Wide X 48" Long
- Discharge Worktable, 50" Wide X 96" Long
- Hydraulic Holddown, Saw Vise
- High Speed Drive, Roller Guides
- Hydraulic Chip Conveyor

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

