



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com

2013

W. F. WELLS MODEL S-40-3C (6° Cant)

Specifications

Capacity	Rectangular at 90° 37" H X 40" W	
	Rectangular at 45° 37" H X 24" W	
Weight Capacity	15,000 lbs	
Blade Speed	60-500 SFPM	
Blade Size	2" X .063" X 29'	
Blade Guide	Carbide Blocks, Spring Tensioned with Idle Roller Back-up	
Blade Tension	Hydraulic	
Bandwheel Size	42"	<u>Voltage</u>
Vise	Hydraulic	208-60-3
Blade Drive	15 HP, AC Vector Drive	230-60-3
Hydraulic Drive	5 HP	460-60-3
Sawing Force	0-1,000 lbs	575-60-3
Coolant Capacity	15 Gallons	
Hydraulic Capacity	20 Gallons	
Work Height	34"	
Outfeed Table	24" X 40"	
Vise Jaw Height	24"	
Hydraulic Powered Blade Brush		
Hydraulic Positioned Guide Arm		
Blade Tension Indicator		
Blade Break/Stall Switch		
Shipping Weight	9,200 lbs Shipping Dimensions (Approx) 175"L x 55"W x 130"H	
Electrics	Wired to NFPA 79 Machine Tool Standards	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Discharge Worktable 40" Wide X 56" Long
- Hydraulic Chip Conveyor
- Hydraulic Holddown, Saw Vise
- Outboard Vise with Hydraulic Holddown
- Outboard Vise
- High Speed Drive & Guides (1½" Blade) 400-3000 SFPM
- Hydraulic Powered Conveyor 40" X 10'
- Non-Powered Conveyor 40" X 5'
- Non-Powered Conveyor 40" X 10'

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

Distributed By:

Tool Technology
 Distributors, Inc.

40 YEARS ANNIVERSARY

P: 510-656-8220
 P: 800-335-8437
 F: 510-656-2458
 E: info@tooltechnology.com
 W: www.tooltechnology.com

MADE IN USA