



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013

**W. F. WELLS MODEL S-40-4**

**Specifications**

Capacity .....	Rectangular at 90° 40" H x 40" W @ 45° 40" H x 24" W	
Weight Capacity .....	15,000 lbs	
Blade Speed.....	60-500 SFPM	
Blade Size .....	2 <sup>5</sup> / <sub>8</sub> " X .063" X 29'	
Blade Guide.....	Carbide Blocks, Spring Tensioned	
Blade Tension.....	Hydraulic	
Bandwheel Size.....	42"	<b><u>Voltage</u></b>
Vise .....	Hydraulic Full Stroke	208-60-3
Blade Drive.....	15 HP, AC Vector Drive	230-60-3
Positive Sawing Force .....	0-1000 lbs	460-60-3
Coolant Capacity .....	20 Gallons	575-60-3
Hydraulic Capacity.....	20 Gallons	
Hydraulic Drive .....	5 HP Motor	
Work Height.....	28"	
Vise Jaw Height.....	24"	
Hydraulic Chip Conveyor		
Hydraulic Powered Blade Brush		
Hydraulic Guide Arm Positioning		
Blade Tension Indicator		
Blade Break/Stall Switch		
Shipping Weight .....	10,500 lbs	Shipping Dimensions (Approx) 175"L x 55"W x 130"H
Electrics.....	LED Blade Speed Indicator, LED Positive Feed Readout	
	Wired to NFPA 79 Machine Tool Standards	

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

- Discharge Worktable 40" W X 56" L
- Hydraulic Holddown, Saw Vise
- Outboard Vise with Hydraulic Holddown
- Outboard Vise
- Hydraulic Powered Conveyor 40" X 10'
- Non-Powered Conveyor 40" X 5'
- Non-Powered Conveyor 40" X 10'
- Roller Bed Inserts (3<sup>1</sup>/<sub>2</sub>" X .300" Rollers - 2 Req'd)
- High Speed Drive & Guides (1<sup>1</sup>/<sub>2</sub>" Blade) 400-3000 SFPM

**Consult Factory For Additional Accessories**

\*Prices and specifications subject to change without notice

Distributed By:

**Tool Technology**  
 Distributors, Inc.

40 YEARS ANNIVERSARY

P: 510-656-8220  
 P: 800-335-8437  
 F: 510-656-2458  
 E: info@tooltechnology.com  
 W: www.tooltechnology.com

**MADE IN USA**