



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013

**W.F. WELLS MODEL W-10-2**

**Specifications**

Capacity.....	Rectangular @ 90° 10" High x 17" Wide, Round @ 90° 10" Dia. Rectangular @ 45° 10" High X 7½" Wide Round @ 45° 7½" Dia.	
Weight Capacity.....	5,000 lbs	
Blade Speed.....	60-500 SFPM	
Blade Size.....	1" X .035" X 11'-11"	
Blade Guide.....	Carbide Block	
Blade Tension.....	Hydraulic, Console Controlled	
Bandwheel Size.....	14½"	<b><u>Voltage</u></b>
Vise.....	Hydraulic, Full Stroke	208-60-3
Blade Drive.....	5 HP, AC Vector Drive	230-60-3
Sawing Force.....	Hydraulic 0-750 lbs	460-60-3
Coolant Capacity.....	15 Gallons	575-60-3 (2HP)
Hydraulic Capacity.....	20 Gallons	
Hydraulic Drive.....	2 HP Motor	
Work Height.....	26"	
Shipping Weight.....	1,975 lbs	
Electrics.....	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	97" Length x 49" Width x 65" Height	

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

- Discharge Worktable, 20" W x 48" L with Stock Stop
- Work Light, Wired In
- Automatic Length Stop Assembly
- Blade Break/Stall Switch
- Hydraulic Chip Conveyor, Auger Style
- Hydraulic Holddown, Saw Vise
- Stock Stand, 6" Wide (Heavy Duty)
- Stock Stand, 12" Wide (Heavy Duty)
- High Speed Drive & Guide 400-3000 SFPM, ¾" Blade
- Free Standing Roller Stock Conveyors, 6" Centers:
- 18" X 5' X 2,500 lbs Cap. Distributed Weight
- 18" X 10' X 5,000 lbs Cap. Distributed Weight

**Consult Factory For Additional Accessories**

\*Prices and specifications subject to change without notice

Distributed By:



**Tool Technology**  
Distributors, Inc.

P: 510-656-8220  
 P: 800-335-8437  
 F: 510-656-2458  
 E: [info@tooltechnology.com](mailto:info@tooltechnology.com)  
 W: [www.tooltechnology.com](http://www.tooltechnology.com)

**MADE IN USA**