



**W.F. WELLS®**

# Model X-Special

Special Application  
Trim Saw



**MADE IN THE USA**



## MACHINE SPECIFICATIONS

Capacity	40" High x 40" Wide x 35" Length
Weight Capacity	10,000 lbs
Blade Speed	330-2000 SFPM
Blade Size	1¼" X .040" X 25' (35-40 Grit)
Blade Guide	High Speed Rollers
Blade Tension	Automatic Preset, Hydraulic
Vise	Vertical Holddown
Blade Drive	10 HP, AC Vector Drive
Sawing Force	Ball Screw Positive Downfeed
Coolant Capacity	20 Gallons
Hydraulic Capacity	20 Gallons
Hydraulic Drive	5 HP Motor
Work Height	112"
Shipping Weight	7,500 lbs
Electrics	Fused Disconnect, 115 Volt Controls
Table Dimensions	30" High Saw Bed/Fixture 36" Deep (35" Cut) 30" Wide 30" From Blade to Front of Worktable
Ship Dimensions	Across Front – 13' 6" Front to Back – 66" Height – 112"

## STANDARD EQUIPMENT

- 1¼" Diamond Segmented Blade
- Laser Shadow Line
- Vertical Support Plate for Top Cap of Ingot
- Ball Screw Positive Downfeed
- High Speed Option, 330-2000 SFPM
- All Motors and Controls
- Fused Disconnect
- Broken Blade Automatic Shutoff
- Console Controlled Blade Speed w/ Digital Indicator
- AC Vector Drive
- Hydraulic Blade Tension with Indicator
- Electronic Door Safety Interlocks
- Operator Manual and Parts List
- Special Full Stroke Hydraulic Holddown V-Configuration with Removable V-Block Holder

Distributed By:



P: 510-656-8220  
P: 800-335-8437  
F: 510-656-2458  
E: info@tooltechnology.com  
W: www.tooltechnology.com

**\*Specifications subject to change without notice**

## W.F. Wells, Inc.

16645 Heimbach Road • Three Rivers, MI 49093

Phone: (269) 279-5123 • Fax: (269) 279-6337

Web page: [www.wfwells.com](http://www.wfwells.com) • E-mail: [info@wfwells.com](mailto:info@wfwells.com)